



Tri-Flex 2 Master Control Panel, Metric 220vAC

Code: [25-0697/01](#)

Product Group: [Tri-Flex 2 Master Control Panel](#)

Standards

ASTM D2850, ASTM D4767, ASTM D7181, ASTM D5084, AASHTO T296, AASHTO T297

Further Information

220vAC, 50/60 Hz, 1 \emptyset .

Specification

Measurement Range	10-4 to 10-10 cm/sec.
Master Regulator	2 to 150 psi (14 -1,034 kPa), dual scale.
Master Pressure Gauge	2 to 160 psi (14 -1,103 kPa), dual scale.
Master Vacuum Gauge	0 to -30 inches of Hg (0-100 kPa), dual scale.
Digital Pressure Meter	English: 2 to 15 0 psi range; \pm 0.1 psi; \pm 0.25 % accuracy full scale. Metric: 14 to 1,034 kPa range; \pm 1 kPa; \pm 0.25 % accuracy full scale.
Burette Pressure Regulators	Three; 2 to 15 0 psi (14 -1,034 kPa).
Burette/Annulus	Three; 25 /400 ml capacity with 0.1 ml burette graduations.
Utilities Required	Water, vacuum, Dry air pressure, drain and AC power supply.
Dimensions	21 " w. x 36-3/4" h. x 7" d. (17" d. with legs); (533 x 933 x 178 mm).

Weight

Net 50 lbs. (22 .7 kg).

Accessories



Auxiliary Control Panel

Code: [25-0699](#)



Pressure Interface Chamber

Code: [25-0695](#)



Tri-Flex 2 Master Control Panel, English 110vAC

Code: [25-0696/02](#)



Tri-Flex 2 Master Control Panel, English 220vAC

Code: [25-0696/01](#)



Tri-Flex 2 Master Control Panel, Metric 110vAC

Code: [25-0697/02](#)



Tri-Flex 2 Water De-airing Tank System

Code: [25-0698](#)

Alternatives



Auxiliary Control Panel

Code: [25-0699](#)



Pressure Interface Chamber

Code: [25-0695](#)



Tri-Flex 2 Master Control Panel, English 110vAC

Code: [25-0696/02](#)



Tri-Flex 2 Master Control Panel, English 220vAC

Code: [25-0696/01](#)



Tri-Flex 2 Master Control Panel, Metric 110vAC

Code: [25-0697/02](#)



Tri-Flex 2 Water De-airing Tank System

Code: [25-0698](#)