



Standard Penetrometer

Code: [46-5290](#)

Product Group: [Asphalt Penetrometer](#), [Bitumen Penetration Test](#), [Penetration Test](#)

Penetration readings are quickly taken using this simple to operate apparatus. The 150 mm diameter dial is graduated in 400 divisions of 0.1 mm. Supplied without needles and penetration tins.

Standards

BS 2000-49, EN 1426, EN 13179-2, IP 49, ASTM D5, AASHTO T49

Further Information

Model shown with sample container; not included, order separately.

Specification

Dial Indicator	6" (150 mm) diam.; 400 mm x 0.1 mm.
Plunger Weight	47.5 g.
Needle	ASTM Style (non-certified); one included.
Plunger Release	Manual mechanism.
Weight	Net 18 lbs. (8.2 kg).

Accessories




ASTM (NIST Certified) Penetration Needle

Code: [46-5297](#)



Constant Temperature Bath 21 - 56°C

Code: [46-5500/01](#)



Penetration Needle

Code: [46-5360/10](#)



Penetration Tin

Code: [46-5860](#)



Penetration Tin

Code: [46-5861](#)



Transfer Dish

Code: [46-5800](#)

Spares/Consumables



ASTM (Non-Certified) Penetration Needle

Code: [46-5290/10](#)