



Capping Compound Warming Pots 110vAC

Code: [34-6125/02](#)

Product Group: [Capping Compound Warming Pots](#)

4 Qt. (3.7 liter) capacity.

Further Information

110vAC, 50/60

Hz, 1ø. 1,250 Watts.110vAC, 50/60

Hz, 1ø. 1,250 Watts.110vAC, 50/60

Hz, 1ø. 1,250 Watts.110vAC, 50/60

Hz, 1ø. 1,250 Watts.110vAC, 50/60

Hz, 1ø. 1,250 Watts.110vAC, 50/60

Hz, 1ø. 1,250 Watts.110vAC, 50/60

Hz, 1ø. 1,250 Watts.

Specification


Capacity	4 qt. (3.7 liters).
Temperature Range	150Â°F to 45 0Â°F (65Â°C to 25 0Â°C).
Control	Adjustable, automatic thermostat with pilot light.
Construction	Round aluminum pot with steel jacket; with cover.
Inside Dimensions	8â diam. x 5-1/2â d. (203 x 140 mm).
Outside Dimensions	9â diam. x 10â h. (229 x 254 mm).
Weights	Shpg. 13 lbs. (5.9 kg).

Accessories



Capping Ladle


Code: [81-0701](#)



Flake Capping Compound to ASTM C617 22Kg


Code: [34-6100](#)

Alternatives



4" Compression Pads 60 Durometer

Code: [34-6132/10](#)



4" Compression Pads 70 Durometer

Code: [34-6132/12](#)




4" Retaining Caps

Code: [34-6132](#)



6" Compression Pads 60 Durometer

Code: [34-6134/10](#)



6" Compression Pads 70 Durometer

Code: [34-6134/12](#)