



Non-Nuclear Asphalt Density Gauge

Code: 47-1000

Product Group: [Aggregate Crushing Value \(ACV\) and Ten Percent Fines Value \(TFV\)](#), [Asphalt Density Gauge](#)

Full colour graphics driven user interface, 480 x 640 VGA touch screen display with LED backlight for easy visibility.

New status bar feature, displays GPS status, battery voltage, low battery and date and time.

Rugged new case design made from 0.90" 5052 aluminum, powder-coated gloss black with green reflective vinyl graphics increasing driver awareness to road worked at night.

New Data Management Feature, quickly access, download or delete your project data.

Ability to upload and download files to the PQI via USB drive.

Fast, reliable, accurate and repeatable readings in real time, user friendly, in-process, cost effective tool for any crew member.

No badges or licenses and no storage or transport concerns.

Further Information

OPERATIONAL SPECIFICATIONS:

MODES:

Single: Reading time less than five (5) seconds. Stores Data.

Average: Averages five (5) readings and stores data including date and time. Stores thousands records.

Continuous: Instantaneous density readings

Segregation: Identifies variations in material density associated with segregation

FUNCTIONS:

- Density, % compaction

- Integrated temperature sensing: Real time temperature display 0 degrees fahrenheit to 350 degrees fahrenheit

CALIBRATION MODES:

- Normal correlation offset of cores

MEASUREMENT SPECIFICATIONS:

- Sensing Area: 11in diameter base allows optimum measurement on fine and coarse material types
- Measurement depth: User selected and adjustable from 1 in. to 4 in.
- Measurement display: Density, % compaction, surface temperature, mix name & project name

MECHANICAL SPECIFICATIONS:

- Unit weight: 14.2 lbs
- Unit dimensions: 11 in x 11 in x 12 in high with handle extensions 29 in high
- Shipping weight w case: 49 lbs (22.22kg)
- Shipping Dimensions: 17.5 in x 18.5 in x 20 in

ELECTRICAL SPECIFICATIONS:


- Microprocessor controlled
- CE mark: complies with EN61000-4-2, 61000-4-3, 61000-4-8
- Battery 14.0 Amp-hr NiMH, 7.2 volt
- Recharge time: 4 hours
- Battery charger: Self contained CE & UL certified universal AC charger, DC charger
- Computer ports: 1 USB port

OPERATIONAL FEATURES:

- Display: Full color graphics driven user interface, 480 x 640 VGA touch screen display with LED backlight for easy visibility in daylight or dark situations
- Status Bar: Displays GPS status, data save status battery voltage, low battery and date and time
- Project details: Stores up to 10 projects with details
- Mix details: Stores up to 20 mixes, details include (MTD, mix name, stone size, depth, offset, operator name)
- Data logging: When enabled, stores all measurements taken in single or average modes (status bar icon)
- Reports: Easily download data to be imported into excel
- GPS control: When activated will display latitude and longitude positions, number of satellites the gauge is connected to as well as the UTC date and time, also available in UTM format. GPS information will store with each measurement when data save and GPS feature is enabled, (status bar icon).
- Update Software: One touch upload of new software using a USB memory stick
- Data Management: Quickly access, download or delete your project data

- Set time & date: Quick time and date setup, MM/DD/YY and DD/MM/YY formats
- Units: Interchangeable settings for Density (kg/m³, lb/ft³), temp, depth and stone size
- Standardization: While gauge is still in the case, a quick one touch measurement will insure the gauge is still in proper working mode
- Calculator: Built in four function calculator
- Enhanced customer support: diagnostics screen to aid in factory support
- User programmable target density: Used for calculating % compaction
- User Changeable battery: easily change batteries in the field

Spares/Consumables



Rubber Washer for Compaction Rammers

Code: [1399A0011](#)