## **Product Sheet**



# Digital pH/Temp/mV Meter with electrode, carrying case and pH 4 & 7 buffers

Code: 430-020 Product Group: Paqualab Test Meters

reduct creap. require rest motors

Robust waterproof case offering IP66/67 protection

Manual/automatic temperature compensation

Easy to use re-calibration function

The 430-020 pH meter is a three-in-one instrument that features a large easy to read, LCD display that indicates pH over the range of -2 to 16 pH with a resolution of 0.01 pH, mV over the range of -1000 to 1000 mV and temperature over the range of -39.9 to 149.9°C with a resolution of 0.1°C. The LCD display features both low battery indication and a user selectable backlight.

The pH readings are either manually or automatically temperature compensated over the range of 0 to 100°C. To automatically compensate, it is necessary to utilise a thermistor temperature probe. Each unit incorporates an auto-power off facility that automatically turns the instrument off after ten minutes, maximising battery life.

The 430-020 has an integrated rubber seal to ensure complete water resistance and helps to reduce the possiblity of damage in harsh environments. At the touch of a button, the instrument will automatically re-calibrate (two-point autocal) itself when used in conjunction with pH buffer solutions.

Each unit incorporates an easy to use BNC connector and Lumberg screw-locking type connector.

#### **Further Information**

#### Specification

Range -2 to 16 pH ± 1000 mV -39.9 to 149.9 °C Battery Battery Life Sensor Type Display Dimensions ResolutionAccuracy0.01 pH $\pm 0.02 \text{ pH}$ 1 mV $\pm 1 \text{ mV}$  $0.1 ^{\circ}\text{C}$  $\pm 0.4 ^{\circ}\text{C}$  (-10 to 70  $^{\circ}\text{C}$ ) $3 \times 1.5 \text{ volt AAA}$ Maximum 5 years (2500 hours)Combination electrode/ thermistor12 mm LCD $32 \times 71 \times 141 \text{ mm}$ 



www.ele.com +44 (0) 01525 249 200



Weight

230 grams

### Spares/Consumables



Spare pH electrode for use with 430-020 meter

Code: 430-020/10

